Technical Specifications

Model t760i	PN217AA
Processor & Speed	Intel® Pentium® 4(P)540 Processor – 3.2GHz/800HT
	LGA775
Chipset	Intel® 915G
Motherboard	Grouper-GL8E (PTGD1-LA)
RAM	256/3200 MB 400 DDR SDRAM
Maximum	3 GB
Sockets	Four 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
Free DIMM Sockets	Three
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	16KB Data Cache + Trace Cache L1, 1MB L2 Integrated
- Autile	on Processor module
Hard Drive	160 GB (7200 RPM) SATA
Optical Drive	
Transfer rates	8x DVD(+/-)R/RW DL Drive Write: Up to 40x (CD-R)
Transfer rates	Write: Up to 40x (CD-R) Write: Up to 24x (CD-RW)
	Write: Up to 8x (DVD(+/-)R)
	Write: Up to 4x (DVD(+/-)RW)
	Write: Up to 2.4x (DVD+R DL)
	Read: Up to 40x (CD)
	Read: Up to 12x (DVD)
Diskette Drive	3.5" (1.44MB)
9 in 1 Card Reader	Compact Flash I/II, Memory Stick/PRO, MMC/SD, Smart
, cara nous.	Media, xD, Microdrive
Fax/Data Modem	V.90 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V .42
EIA Fax Commands	Class 1
Video Graphics	PCI Express 16x Graphics Card
Controller	ATI RV370E
Video Memory	128 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - PAL
TV Tuner	TV Tuner Card w/FM
Network Card	10/100 BaseT, Integrated
	10/100 base1, integrated
1004.6	IEEE 1004
1394 Card	IEEE-1394
Sound	Azalia 7.1 Audio, Integrated on MB
Sound Controller	Azalia 7.1 Audio, Integrated on MB Realtek ALC880
Sound Controller Chassis	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU
Sound Controller Chassis USB Interface Specification	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU USB 2.0
Sound Controller Chassis	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU USB 2.0 4= USB, 1=1394, Serial, Parallel,
Controller Chassis USB Interface Specification External I/O Rear Connectors	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU USB 2.0 4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone
Controller Chassis USB Interface Specification External I/O Rear Connectors External I/O Front Connectors	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU USB 2.0 4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone 2= USB, 1= 1394, Microphone, Headphone
Sound Controller Chassis USB Interface Specification External I/O Rear Connectors External I/O Front Connectors Expansion Slots (Total)	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU USB 2.0 4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone 2= USB, 1= 1394, Microphone, Headphone 3= PCI, 1= PCI Express
Sound Controller Chassis USB Interface Specification External I/O Rear Connectors External I/O Front Connectors Expansion Slots (Total) Expansion Slots (FREE)	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU USB 2.0 4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone 2= USB, 1= 1394, Microphone, Headphone 3= PCI, 1= PCI Express 1= PCI
Sound Controller Chassis USB Interface Specification External I/O Rear Connectors External I/O Front Connectors Expansion Slots (Total) Expansion Slots (FREE) Drive Bays (Total)	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU USB 2.0 4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone 2= USB, 1= 1394, Microphone, Headphone 3= PCI, 1= PCI Express 1= PCI Two 5.25" external, One 3.5" internal
Sound Controller Chassis USB Interface Specification External I/O Rear Connectors External I/O Front Connectors Expansion Slots (Total) Expansion Slots (FREE) Drive Bays (Total) Drive Bays (FREE)	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU USB 2.0 4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone 2= USB, 1= 1394, Microphone, Headphone 3= PCI, 1= PCI Express 1= PCI Two 5.25" external, One 3.5" internal One 5.25" external
Sound Controller Chassis USB Interface Specification External I/O Rear Connectors External I/O Front Connectors Expansion Slots (Total) Expansion Slots (FREE) Drive Bays (Total)	Azalia 7.1 Audio, Integrated on MB Realtek ALC880 Jaguar, 300B HV PSU USB 2.0 4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone 2= USB, 1= 1394, Microphone, Headphone 3= PCI, 1= PCI Express 1= PCI Two 5.25" external, One 3.5" internal